

Declare. SM

SOLICOR Compact: 560, 596, 597, 598, 599 (Excludes finishes 31, 95, 96) **Wilsonart**

Final Assembly: Fletcher, North Carolina, USA

Life Expectancy: 20-50 Year(s)

Embodied Carbon: 2.91E+01 KG CO2 EQ

Declared Unit: ONE SQUARE METER OF PRODUCT

End of Life Options: Landfill (100%)

EU CoC Screened: Does Not Contain

Ingredients:

SOLICOR Compact: Wood / Cellulose Fiber (Kraft / Decorative / Overlay); **Melamine Resin¹**; Titanium dioxide; Black Pigment; Grit; Release

¹LBC Temp Exception RL-009 - Formaldehyde

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Product Available with FSC Chain of Custody

WIL-0004

EXP. 01 MAR 2027

SCREENED: 10 MAR 2026

Original Issue Date: 2023