

Declare. SM

SOLICOR Laminate: 160, 161 (Excludes 31 finish) **Wilsonart**

Final Assembly: Temple, Texas, USA

Life Expectancy: 20-50 Year(s)

Embodied Carbon: 1.99E+00 KG CO2 EQ

Declared Unit: 1 SQUARE METER OF PRODUCT

End of Life Options: Landfill (100%)

EU CoC Screened: Does Not Contain

Ingredients:

SOLICOR Laminate: Wood / Cellulose Fiber (Kraft / Decorative / Overlay); **Melamine Resin¹**; **Phenolic Resin¹**; Titanium dioxide; Black Pigment; Colorant; Grit; Release

¹LBC Temp Exception RL-009 - Formaldehyde

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Product Available with FSC Chain of Custody

WIL-0006

EXP. 01 MAR 2027

SCREENED: 10 MAR 2026

Original Issue Date: 2023