

1. **Manufacturer**

Wilsonart  
2501 Wilsonart Drive  
P.O. Box 6110  
Temple, Texas 76503-6110  
Phone: (254) 207-7000; (800) 433-3222  
Fax: (254) 207-2384  
Web Site: [www.wilsonart.com](http://www.wilsonart.com)

2. **Product Description**

Wilsonart® RE-COVER™ Laminate is a self-adhesive High Pressure Laminate designed for resurfacing over an existing High Pressure Decorative Laminate, Low Pressure Laminate (melamine), or painted/stained wood surface.

**Recommended Uses**

RE-COVER Laminate is suitable for flatwork use on fine quality residential and contract furniture, casework designs, as well as architectural applications for wainscoting, valances, cornices, interior doors and divider systems. RE-COVER Laminate must be bonded to a suitable substrate such as particleboard, medium density fiberboard, plywood with one “A” face, previously bonded high pressure, low pressure decorative laminate (melamine board), or a painted/stained wood surface.

- **RE-COVER Decorative Metals Type 480** is used for retail facilities, hotel and office lobbies, theaters and restaurants. Type 480 is used when Wilsonart® Decorative Metal are requested. Wilsonart Decorative Metals available with RE-COVER are Types 415 and 419. Type 480 is intended for vertical applications only.
- **Vertical Surface (VGS) Type 735** is the usual choice to surface cabinet walls, doors and drawer panels. It often appears on the vertical surfaces of desks, restaurants booths and maitre d’ stations, and as architectural cladding. Type 735 is intended for vertical applications where a functional, durable, decorative surface must absorb somewhat less impact than a comparable horizontal surface.
- **RE-COVER Chalkboard Type 737** is an innovative new option for laminate installation and resurfacing for panels, desks, tables, doors, and walls. Wilsonart RE-COVER Chalkboard Laminate transforms any surface into a writable chalkboard surface.
- **RE-COVER Traceless Type 738** is suitable for use in retail, office furniture, manufactured housing, hospitality, casework, countertops, and interior doors and also for architectural application on wainscoting, valances, and divider systems.
- **RE-COVER Virtual Design Library (VDL) I Type 762** is used for work surfaces on islands, counters, vanities, desks and tables. Type 762 is used when patterns from Group I of the Virtual Design Library (VDL I) is specified. Type 762 is intended for vertical applications where a functional, durable, decorative surface must absorb somewhat less impact than a comparable horizontal surface.
- **RE-COVER Virtual Design Library (VDL) II Type 764** is used for work surfaces on islands, counters, vanities, desks and tables. Type 764 is used when patterns from Group II of the Virtual Design Library (VDL II) is specified. Type 764 is intended for vertical applications where a functional, durable, decorative surface must absorb somewhat less impact than a comparable horizontal surface.

- **RE-COVER WilsonartXYou (WxY) Type 767** is used for work surfaces on islands, counters, vanities, desks and tables. Type 767 is used when a custom pattern is created and specified. Type 767 is intended for vertical applications where a functional, durable, decorative surface must absorb somewhat less impact than a comparable horizontal surface.
- **RE-COVER High Definition® (HGL) Type 776** is used for work surfaces on islands, counters, vanities, desks and tables. Wilsonart® HD® Surfaces combine the most dramatic designs and textures with Antimicrobial Protection and Enhanced Scratch and Scuff-Resistant AEON™ Technology to produce the best laminate for countertops and work surfaces. Type 776 is made for both horizontal and vertical interior applications where the surface must be functional, durable and decorative.

**Product Composition**

Decorative surface papers impregnated with melamine resins are pressed over kraft paper core sheets impregnated with phenolic resin. These sheets are then bonded at pressures greater than 1000 pounds per square inch at temperatures approaching 300°F (149°C). Finished sheets are trimmed, sanded, and then coated with an acrylic sheet adhesive.

**Basic Limitations**

Wilsonart RE-COVER Laminate is for interior use only and is not recommended for direct application to gypsum, also known as Sheetrock®. It is not structural material and must be bonded to a suitable substrate such as particleboard, medium density fiberboard; plywood with one “A” face, previously bonded high pressure or low pressure decorative laminate (melamine board).

Do not subject Wilsonart RE-COVER Laminate to extremes in humidity, temperatures higher than 150°F for substantial periods of time, or intense, continuous, direct sunlight.

**Patterns, Colors, and Finishes**

Available in the full range of Wilsonart products including High Pressure Laminate, Chalkboard, Decorative Metals, and Custom laminate. Please see actual sample before specifying.

**3. Technical Data**

**Standard Sheet Widths**

36"	48"	60"
914mm	1219mm	1524mm

**Standard Sheet Lengths**

96"	120"	144"
2438mm	3048mm	3658mm

*NOTE: Not all sizes are available from stock; contact your Wilsonart representative for details on local availability. Minimums apply to non-standard designs and finishes. Please check with your Wilsonart representative.*

**Thickness and Weight (with Release Paper)**

Description	480	735	737	762/764/767	776
Thickness	0.035" ± 0.005" (0.89 ± 0.13mm)	0.038" ± 0.005" (0.97 ± 0.13mm)	0.049" ± 0.005" (1.24 ± 0.13mm)	0.038" ± 0.005" (0.97 ± 0.13mm)	0.049" ± 0.005" (1.24 ± 0.13mm)
Weight per square foot	0.402 lbs.	0.235 lbs.	0.371 lbs.	0.235 lbs.	0.309 lbs.

### Physical Properties

Please see the coordinating products Physical Properties for more information.

<b>RE-COVER Types</b>	<b>480</b>	<b>735</b>	<b>737</b>	<b>762/764/767</b>	<b>776</b>
<b>Coordinating Types</b>	415/419	335	137	362/364/367	376

### Codes and Certifications

#### General Standards

Wilsonart laminates conform to the voluntary standards of the American National Standards Institute, for thickness, performance properties and appearance. Various grades of Wilsonart laminates meet or exceed the International Standards Organization specifications as found in ISO 4586, titled "High-Pressure Decorative Laminate (HPDL) – Sheets Based on Thermosetting Resins – Part I: specifications."

4. [Warranty](#)

5. [Maintenance](#)

6. **Technical Services**

For samples, literature, questions or technical assistance, please contact our toll-free Hotline at (800) 433-3222, Monday through Friday, 8 am – 5 pm, CST.

#### Specification Form

Surface shall be Wilsonart® RE-COVER Laminate  
Produced by Wilsonart LLC,  
Temple, Texas 76503-6110

Type: Specify 480, 735, 737, 762, 764, 767, or 776

#### Surface

Color Number: \_\_\_\_\_

Color Name: \_\_\_\_\_

#### Finish

Number: \_\_\_\_\_

Name: \_\_\_\_\_

#### Edge Trim

Color Number: \_\_\_\_\_

Color Name: \_\_\_\_\_

Material shall equal or exceed performance standards set by the American National Standards Institute/National Electrical Manufacturers Association (ANSI/NEMA) LD3-2005 for high-pressure laminate. Fabrication shall comply with "Architectural Woodwork Quality Standards, Guide Specifications and Quality Certification Program" guidelines of the Architectural Woodwork Institute.

Wilsonart® RE-COVER™ Technical Data

Revised: February 5, 2018

© 2018, Wilsonart LLC