

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Wilsonart 1800/1801 Adhesive
Product form : Mixtures

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive for laminate

1.3. Details of the supplier of the safety data sheet

Manufacturer:

Wilsonart LLC
P.O. Box 6110
Temple, TX 76503-6110
Information phone: 800-433-3222 (USA)
In Case of Emergency Contact CHEMTREC (International): 703-527-3887

Canadian Supplier:

Wilsonart Canada
380 Courtney Park Dr. East, Unit A
Mississauga, Ontario L5T 2S5
905-565-7855

1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Liq. 2 H225
Eye Irrit. 2A H319
Skin Sens. 1 H317
Repr. 2 H361
STOT SE 3 H336

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

H225 - Highly flammable liquid and vapour
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing mist, spray, vapours
P264 - Wash hands, forearms and face, clothing thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see first aid instructions on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use foam, dry chemical, carbon dioxide (CO₂) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
tert-Butyl acetate	(CAS No) 540-88-5	52.45
Acetone	(CAS No) 67-64-1	24.02
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	2.12
Cyclohexane	(CAS No) 110-82-7	1.06
Pentane	(CAS No) 109-66-0	1.06
Isopentane	(CAS No) 78-78-4	1.06
Rosin	(CAS No) 8050-09-7	0.21
Naphtha, petroleum, hydrotreated light	(CAS No) 64742-49-0	0.13
Toluene	(CAS No) 108-88-3	0.98
Hexane	(CAS No) 110-54-3	0.12
tert-Butyl alcohol	(CAS No) 75-65-0	0.26

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause an allergic skin reaction. May cause respiratory irritation.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Direct contact with eyes is likely to be irritating.

Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide.

Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : Static discharge may serve as an ignition source for this product.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Prohibit smoking in storage area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tert-Butyl acetate (540-88-5)	
Alberta	200 ppm; 950 mg/m ³ TWA
British Columbia	200 ppm TWA
Manitoba	200 ppm TWA
New Brunswick	200 ppm TWA; 950 mg/m ³ TWA
Newfoundland and Labrador	200 ppm TWA
Northwest Territories	200 ppm TWA; 250 ppm STEL

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

Nova Scotia	200 ppm TWA
Nunavut	200 ppm TWA; 250 ppm STEL
Ontario	200 ppm TWA; 300 ppm STEL
Prince Edward Island	200 ppm TWA
Quebec	200 ppm; 950 mg/m ³ TWA
Saskatchewan	200 ppm TWA; 250 ppm STEL
Yukon	200 ppm, 950 mg/m ³ TWA 250 ppm, 1180 mg/m ³ STEL

Acetone (67-64-1)

Alberta	500 ppm TWA; 1200 mg/m ³ TWA 750 ppm STEL; 1800 mg/m ³ STEL
British Columbia	250 ppm TWA; 500 ppm STEL
Manitoba	250 ppm TWA; 500 ppm STEL
New Brunswick	500 ppm TWA, 1188 mg/m ³ TWA; 750 ppm STEL; 1782 mg/m ³ STEL
Newfoundland and Labrador	250 ppm TWA; 500 ppm STEL
Northwest Territories	500 ppm TWA; 750 ppm STEL
Nova Scotia	250 ppm TWA; 500 ppm STEL
Nunavut	500 ppm TWA; 750 ppm STEL
Ontario	500 ppm TWA; 750 ppm STEL
Prince Edward Island	250 ppm TWA; 500 ppm STEL
Quebec	750 ppm, 1780 mg/m ³ TWA; 1000 ppm, 2380 mg/m ³ STEL
Saskatchewan	500 ppm TWA; 750 ppm STEL
Yukon	1000 ppm, 2400 mg/m ³ TWA 1250 ppm, 3000 mg/m ³ STEL

Tert-Butanol (75-65-0)

Alberta	100 ppm; 303 mg/m ³ TWA
British Columbia	100 ppm TWA
Manitoba	100 ppm TWA
New Brunswick	100 ppm TWA; 303 mg/m ³ TWA
Newfoundland and Labrador	100 ppm TWA
Northwest Territories	100 ppm TWA; 125 ppm STEL
Nova Scotia	100 ppm TWA
Nunavut	100 ppm TWA; 125 ppm STEL
Ontario	100 ppm TWA
Prince Edward Island	100 ppm TWA
Quebec	100 ppm; 303 mg/m ³ TWA 150 ppm; 455 mg/m ³ STEL
Saskatchewan	100 ppm TWA; 125 ppm STEL
Yukon	100 ppm; 300 mg/m ³ TWA 150 ppm; 450 mg/m ³ STEL

Cyclohexane (110-82-7)

Alberta	100 ppm; 344 mg/m ³ TWA
British Columbia	100 ppm TWA
Manitoba	100 ppm TWA
New Brunswick	300 ppm TWA; 1030 mg/m ³ TWA
Newfoundland and Labrador	100 ppm TWA
Northwest Territories	100 ppm TWA; 150 ppm STEL
Nova Scotia	100 ppm TWA
Nunavut	100 ppm TWA; 150 ppm STEL
Ontario	100 ppm TWA
Prince Edward Island	100 ppm TWA

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

Quebec	300 ppm, 1030 mg/m ³ TWA
Saskatchewan	100 ppm TWA; 150 ppm STEL
Yukon	300 ppm; 1050 mg/m ³ TWA 375 ppm; 1300 mg/m ³ STEL

Isopentane (78-78-4)	
Alberta	600 ppm; 1770 mg/m ³
British Columbia	600 ppm
Manitoba	1000 ppm TWA (listed under Pentane, all isomers)
New Brunswick	OELs not established
Newfoundland and Labrador	1000 ppm TWA (listed under Pentane, all isomers)
Northwest Territories	600 ppm TWA; 750 ppm STEL
Nova Scotia	1000 ppm TWA (listed under Pentane, all isomers)
Nunavut	600 ppm TWA; 750 ppm STEL
Ontario	600 ppm TWA
Prince Edward Island	1000 ppm TWA (listed under Pentane, all isomers)
Quebec	OELs not established
Saskatchewan	600 ppm TWA; 750 ppm STEL
Yukon	OELs not established

Pentane (109-66-0)	
Alberta	600 ppm; 1770 mg/m ³ TWA
British Columbia	600 ppm TWA
Manitoba	1000 ppm TWA (listed under Pentane, all isomers)
New Brunswick	600 ppm TWA; 1770 mg/m ³ TWA 750 ppm STEL; 2210 mg/m ³ STEL
Newfoundland and Labrador	1000 ppm TWA (listed under Pentane, all isomers)
Northwest Territories	600 ppm TWA; 750 ppm STEL
Nova Scotia	1000 ppm TWA (listed under Pentane, all isomers)
Nunavut	600 ppm TWA; 1771 mg/m ³ TWA 750 ppm STEL; 2213 mg/m ³ STEL
Ontario	600 ppm TWA
Prince Edward Island	1000 ppm TWA (listed under Pentane, all isomers)
Quebec	120 ppm; 350 mg/m ³ TWA
Saskatchewan	600 ppm TWA; 750 ppm STEL
Yukon	600 ppm; 1800 mg/m ³ TWA 750 ppm; 2250 mg/m ³ STEL

Toluene (108-88-3)	
Alberta	50 ppm; 188 mg/m ³
British Columbia	20 ppm TWA
Manitoba	20 ppm TWA
New Brunswick	50 ppm; 188 mg/m ³
Newfoundland and Labrador	20 ppm TWA
Northwest Territories	50 ppm TWA; 60 ppm STEL
Nova Scotia	20 ppm TWA
Nunavut	50 ppm TWA; 60 ppm STEL
Ontario	20 ppm TWA
Prince Edward Island	20 ppm TWA
Quebec	OELs not established
Saskatchewan	50 ppm TWA; 60 ppm STEL
Yukon	100 ppm, 375 mg/m ³ TWA; 150 ppm, 560 mg/m ³ STEL

Naphtha, petroleum, hydrotreated light (64742-49-0)	
Alberta	OELs not established

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

British Columbia	OELs not established
Manitoba	OELs not established
New Brunswick	OELs not established
Newfoundland and Labrador	OELs not established
Northwest Territories	OELs not established
Nova Scotia	OELs not established
Nunavut	OELs not established
Ontario	OELs not established
Prince Edward Island	OELs not established
Quebec	OELs not established
Saskatchewan	OELs not established
Yukon	OELs not established
Hexane (110-54-3)	
Alberta	50 ppm; 176 mg/m ³ TWA
British Columbia	20 ppm TWA
Manitoba	50 ppm TWA
New Brunswick	50 ppm TWA; 176 mg/m ³ TWA
Newfoundland and Labrador	50 ppm TWA
Northwest Territories	50 ppm TWA; 62.5 ppm STEL
Nova Scotia	50 ppm TWA
Nunavut	50 ppm TWA; 62.5 ppm STEL
Ontario	50 ppm TWA
Prince Edward Island	50 ppm TWA
Quebec	50 ppm; 176 mg/m ³ TWA
Saskatchewan	50 ppm TWA; 62.5 ppm STEL
Yukon	100 ppm; 360 mg/m ³ TWA 125 ppm; 450 mg/m ³ STEL
Rosin (8050-09-7)	
Alberta	OELs not established
British Columbia	(L)
Manitoba	OELs not established
New Brunswick	OELs not established
Newfoundland and Labrador	Dermal Sensitizer; Respiratory Sensitizer (listed under Rosin core solder thermal decomposition products)
Northwest Territories	OELs not established
Nova Scotia	Dermal Sensitizer; Respiratory Sensitizer (listed under Rosin core solder thermal decomposition products)
Nunavut	OELs not established
Ontario	(L)
Prince Edward Island	OELs not established
Quebec	OELs not established
Saskatchewan	OELs not established
Yukon	OELs not established

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Safety glasses. Gloves. Protective clothing.



Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

Hand protection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
Eye protection	: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
Skin and body protection	: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
Respiratory protection	: Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Red. Yellow brown.
Odor	: Organic solvent.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 76 °C (169 °F)
Flash point	: -14.4 °C Seta Closed Cup (6 °F)
Auto-ignition temperature	: 260 °C (500 °F) (Pentane)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: Greater than air
Relative density	: 0.9
Density	: 7.5 lb/gal
Solubility	: Water: Not soluble in water
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 450 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.26 - 13 vol % LEL - t-Butyl Acetate; UEL - Acetone

9.2. Other information

Other properties	: Percent Volatile: 79%.
------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flame. Ignition sources.

10.5. Incompatible materials

Strong acids and alkalies, oxidizing agents, reducing agents, copper and copper alloys.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Various hydrocarbons.

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Rosin (8050-09-7)	
LD50 oral rat	7600 mg/kg
LD50 dermal rabbit	> 2500 mg/kg
LC50 inhalation rat (mg/l)	1.5 mg/l/4h

Cyclohexane (110-82-7)	
LD50 oral rat	12705 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	13.9 mg/l/4h

Isopentane (78-78-4)	
LC50 inhalation rat (mg/l)	280000 mg/m ³ 4 h

Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	364 g/m ³ 4 h

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h

Hexane (110-54-3)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	48000 ppm/4h

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

Acetone (67-64-1)	
LC50 inhalation rat (mg/l)	50100 mg/m ³

tert-Butyl acetate (540-88-5)	
LC50 inhalation rat (mg/l)	> 2230 mg/m ³ 4 h

tert-Butyl alcohol (75-65-0)	
LD50 oral rat	2200 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	> 10000 ppm/4h
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Direct contact with eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child.

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.

12.2. Persistence and degradability

Wilsonart 1800/1801 Adhesive

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with TDG

Transport document description : UN1133 Adhesives, containing a flammable liquid, 3, II
UN-No.(TDG) : 1133
DOT NA no. : UN1133
Proper Shipping Name (TDG) : Adhesives, containing a flammable liquid
Class (TDG) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (TDG) : 3 - Flammable liquid



Packing group (TDG) : II - Medium Danger
TDG Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
TDG Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
TDG Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information : **Limited Quantity Exception**-flammable liquids in Packing Group II, inner packagings not over 5.0 L (1.3 gallons) net capacity each, 172.102 exception 149,packed in a strong outer packaging.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. Canadian Federal regulations

Wilsonart 1800/1801 Adhesive

All chemical substances in this product are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL) or are exempt.

Wilsonart 1800/1801 Adhesive

Safety Data Sheet

Prepared according to Canadian Hazardous Products Regulations (SOR/2015-17) (WHMIS 2015)

SECTION 16: Other information


Indication of changes : New SDS Created.
: 04/21/17

Other information : Author: MT.

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS III Rating

Health : 2
Flammability : 4
Physical : 0
Personal protection :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product